

YAMAZAKI ET AL. -- 10/658,370  
Attorney Docket No.: 008312-0305862

- Amendment -

### IN THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. *(Cancelled).*

2. *(Currently Amended)* A method of detecting a malfunction in an electric injection-molding machine, the method being applied to ~~the step of ejecting~~ ejection of a molded product by pushing an ejector pin out of a die, the method comprising:

obtaining a pattern ~~showing~~ characterizing torque of an ejector-pin driving motor ~~versus~~ relative to time or a position of an ejector pin based on when a molded product is normally removed;

setting, in advance, at least one monitoring zone based on the pattern and the upper and lower limits of torque in each of the monitoring zones;

monitoring a torque value in each of the monitoring zones during the ~~ejecting~~ step, judging ejection of the molded product and determining that a malfunction ~~occurs~~ has occurred when the torque value falls outside the upper and lower limits of the monitoring zone, and counting the number of malfunctions; and

raising an alarm when the number of malfunctions in during a single ejection step reaches a predetermined number.

3. *(Currently Amended)* A method of detecting a malfunction in an electric injection-molding machine, the method being applied to ~~the step of ejecting~~ ejection of a molded product by pushing an ejector pin out of a die, the method comprising:

obtaining a pattern ~~showing~~ characterizing torque of an ejector-pin driving motor ~~versus~~ relative to time or a position of an ejector pin based on when a molded product is normally removed;

setting, in advance, at least one monitoring zone based on the pattern and the upper and lower limits of torque in each of the monitoring zones;

YAMAZAKI ET AL. -- 10/658,370  
Attorney Docket No.: 008312-0305862

- Amendment -

monitoring a torque value in each of the monitoring zones during the ~~ejecting step, judging ejection of the molded product and determining~~ that a malfunction ~~occurs~~ has occurred when the torque value falls outside the upper and lower limits of the monitoring zone, and counting the number of malfunctions; and

raising an alarm when the number of malfunctions occurring within a predetermined time reaches a predetermined number.

4. *(Cancelled).*

5. *(Currently Amended)* A method of detecting a malfunction in an hydraulic injection-molding machine, the method being applied to ~~the step of ejecting ejection of~~ a molded product by pushing an ejector pin out of a die, the method comprising:

obtaining a pattern ~~showing~~ characterizing hydraulic pressure of an ejector-pin driving hydraulic pump ~~versus~~ relative to time or a position of an ejector pin based on when a molded product is normally removed;

setting, in advance, at least one monitoring zone based on the pattern and the upper and lower limits of hydraulic pressure in each of the monitoring zones;

monitoring a hydraulic pressure value in each of the monitoring zones during the ~~ejecting step, judging ejection of the molded product and determining~~ that a malfunction ~~occurs~~ has occurred when the hydraulic pressure value falls outside the upper and lower limits, and counting the number of malfunctions; and

raising an alarm when the number of malfunctions ~~is~~ during a single ejection step reaches a predetermined number.

6. *(Currently Amended)* A method of detecting a malfunction in a hydraulic injection-molding machine, the method being applied to ~~the step of ejecting ejection of~~ a molded product by pushing an ejector pin out of a die, the method comprising:

obtaining a pattern ~~showing~~ characterizing hydraulic pressure of an ejector-pin driving hydraulic ~~bump~~ pump relative to time or a position of an ejector pin based on when a molded product is normally removed;

YAMAZAKI ET AL. -- 10/658,370

Attorney Docket No.: 008312-0305862- Amendment -

setting, in advance, at least one monitoring zone based on the pattern and the upper and lower limits of hydraulic pressure in each of the monitoring zones; and

monitoring a hydraulic pressure value in each of the monitoring zones during the ~~ejecting step, judging ejection of the molded product and determining that a~~ malfunction occurs when the hydraulic pressure value falls outside the upper and lower limits of the monitoring zone, and counting the number of malfunctions; and

raising an alarm when the number of malfunctions occurring within a predetermined time reaches a predetermined number.